

# PICO

## Top Feed Injector



### Description

The "Pico" top feed injector is a standard production component built to the same automotive standard and specification.

The characteristics of the injector are a fast pulse response, high precision, high dynamic range and optimum fuel atomisation. These are achieved by a high performance ON-OFF actuating electromagnet with opposing expansion poles that moves an internal injector valve on high-precision ground cylindrical slides, and a high precision nozzle.

The injector has a stainless steel body, a fuel-resistant plastic connector, martensitic stainless steel internal valve and an electromagnet with a low carbon content stainless steel armature.

The electrical connection to the control unit is via a Mini-Timer plastic plug.



### Technical Data

#### Performance - Typical

Linearity range ( $T_j = 4$ ms) .....	$\pm 2.5$ %
Max. fuel pressure allowed.....	500 kPa
Maximum duty cycle.....	90 %
Operating temperature range .....	-30..110 °C
Vibration (peak).....	30 g

#### Test conditions

Fluid.....	N-Heptane
density (@ 20°C) .....	0.684 kg/litre
Ambient and fluid temperature .....	23 °C
Power supply .....	14 Vdc
Injection frequency .....	Fully open
Pulse duration .....	n/a
Pressure .....	3 bar

#### Mechanical Characteristics


Height.....	47.2 mm
Outside diameter (connector excluded) .....	15.3 mm
Weight.....	35 g

#### Electrical Characteristics

Connector.....	Mini-Timer 2 way
Power supply .....	8 ± 16 Vdc
Resistance.....	14.5 Ω
Driver type .....	ON-OFF

### Electrical connections

PIN	Description
1	GND
2	+12 V



### Ordering information

Part No	Description	Colour band	Order code
IWP 001	Pico injector – 200 cc/min static flow		214310000110
IWP 006	Pico injector – 226 cc/min static flow	Blue	214310000610
IWP023	Pico injector – 158 cc/min static flow	Green	214310002310
IWP043	Pico injector – 329 cc/min static flow	Brown	214310004310
IWP045	Pico injector – 200 cc/min static flow		214310004510
IWP049	Pico injector – 184 cc/min static flow		214310000490
IWP064	Pico injector – 186 cc/min static flow		214310006400
IWP069	Pico injector – 491 cc/min static flow	Yellow	214310006900

MM Competition Systems Ltd Hyjuniper, Long Lane Shaw, Berkshire, RG14 2TA England	For further details please contact  Tel: +44 (0)8707 444666 Fax: +44 (0)8707 444888 <a href="http://www.mmcompsys.com">www.mmcompsys.com</a> <a href="mailto:mail@mmcompsys.com">mail@mmcompsys.com</a>
---	--